

BOXXER GOLD CORP.

Suite 2300, 635 – 8 Ave. S.W. Calgary, Alberta, Canada T2P 3M3

Tel: (403) 215-5256; Fax: (403)263-8665

July 20, 2006

For Immediate Release

Boxxer Receives Phase I Drilling Assay Results on Boss Property

Calgary, Alberta - Boxxer Gold Corp. (TSXV-"BXX") announces the results of a diamond drilling program on the Boss property located approximately 90 kilometres southwest of Las Vegas, Nevada.

Drilling has confirmed the extension at depth of oxide gold mineralization previously identified by trenching in the Yellowhorse open cut area (see April, 2006 press release). Assay results indicate that gold mineralization, which is hosted in altered granite - syenite porphyry, occurs as a linear-shaped, steeply dipping (average of 60° SW), north to northwest trending zone that is at least 550 feet (~168m) long and averages 78 feet (~24m) in true thickness. The zone was tested to approximately 200 feet down dip where it remains open; laterally it pinches out to the southeast (by Section 355N) but is open along strike to the northwest beyond Section 522N.

A calculated weighted average (uncut) grade for the zone (both trench and drill hole assays) is 0.8g/t Au with a higher-grade portion (Sections 456N, 490N and 522N) averaging 1.03g/t (See Table -1).

The highest-grade material (6g/t up to 151g/t Au) located in the zone thus far occurs as strongly iron ± copper (malachite)-stained, commonly gossanous, structurally – controlled, pods. Locally fine-grained free gold was observed in drill core and also panned from hematitic gossan trench samples.

Approximately 2,100 feet (637m) in 13 shallow holes have been completed and a total of 453 sawed core plus 15 sludge samples collected in this first round of drilling. The five drill fences (Sections 355N, 404N, 456N, 490N, 522N) that were constructed are spaced 120 (36.6m) to 260 feet (79.3m) apart and oriented approximately N65°E; 3 of the 5 fences (Sections 456N, 490N, 522N) were within the open cut area. Each fence consists of a previously dug surface trench (2004 or 2006) that was undercut by 2 to 3 drill holes (See Table -1). Approximately 850 feet (259m) of strike length was tested.

| Table 1 Drillhole fence assay results for Yellowhorse gold zone | | | | | | | | | | |
|--|---------------|---------------|-----------------------|---------|---------------|-----------------|----------------|------------------|-----------------------|-------------|
| Drill Section | Trench or DDH | Hole | From feet | To feet | Interval feet | Interval meters | ~ True | ~True | Weighted Au Assay g/t | |
| | | Angle degrees | | | | | Thickness feet | Thickness meters | | |
| 522N | T-J* | | 0 | 15 | 15 | 4.6 | 13 | 4.0 | 1.03 | |
| | YH06-5 | -65 | 9.5 | 81 | 71.5 | 21.8 | 61.9 | 18.9 | 1.04 | |
| | YH06-5A | -90 | 22 | 107 | 85 | 25.9 | 73.6 | 22.4 | 0.54 | |
| 490N | T-D | | 0 | 147 | 147 | 44.8 | 127 | 38.7 | 0.66 | |
| | YH06-2 | -65 | 11 | 102 | 91 | 27.7 | 78.8 | 24.0 | 1.27 | |
| | YH06-2A | -90 | 52 | 117 | 65 | 19.8 | 56.3 | 17.2 | 1.07 | |
| 456N | T-B | | 0 | 80.5 | 80.5 | 24.5 | 69.7 | 21.3 | 1.85 | |
| | YH06-1 | -45 | 5 | 88.6 | 83.6 | 25.5 | 72.4 | 22.1 | 1.12 | |
| | YH06-1A | -65 | 16.2 | 91 | 74.8 | 22.8 | 64.8 | 19.8 | 1 | |
| | YH06-1B | -90 | 27.2 | 32.2 | 5 | 1.5 | 4.3 | 1.3 | 1.15 | |
| | | | | 47.4 | 57.1 | 9.7 | 3.0 | 8.3 | 2.5 | 0.95 |
| | | | 77.3 | 122 | 44.7 | 13.6 | 38.7 | 11.8 | 1 | |
| 404N | T-H | | 0 | 60 | 60 | 18.3 | 52 | 15.9 | 0.15 | |
| | YH06-3 | -65 | 0 | 115.8 | 115.8 | 35.3 | 103 | 31.4 | 0.213 | |
| | YH06-3A | -90 | 0 | 161 | 161 | 49.1 | 139.4 | 42.5 | 0.21 | |
| | YH06-3B | -45 | no significant values | | | | | | | |
| 355N | T-8 | | 0 | 20 | 20 | 6.1 | 20 | 6.1 | 0.12 | |
| | YH06-4 | -65 | no significant values | | | | | | | |
| | YH06-4A | -90 | no significant values | | | | | | | |
| | YH06-4B | -65 | no significant values | | | | | | | |

Conclusions:

Exploration results indicate mineralization in the Yellowhorse zone displays all the key criteria necessary to form a bulk-mineable oxide gold deposit. This recent drilling program has confirmed potentially commercial gold grades and thicknesses as well as demonstrated continuity to the mineralized zone. Significant size potential of the identified zone is indicated by both the drilling and geophysical surveys.

Exploration Program:

The next stage of exploration in the Yellowhorse area will include diamond drilling to test further the down-dip and lateral extent of the zone of oxide gold mineralization and as well as any associated gold-bearing jasperoid replacement bodies (see April press release).

Sample Preparation and Analysis:

All drill core and sludge samples were prepared at the ALS Chemex laboratory in Elko Nevada. Prepared sample pulps were shipped to ALS Chemex in Vancouver, British Columbia for geochemical analysis (atomic absorption and ICP-AES methods). ALS Chemex's quality system complies with the requirements for the International Standards ISO9001:2000 and ISO 17025:1999. Analytical accuracy and precision are monitored by the use of international and in-house standards. Submittal of blanks along with the collected samples was done on a routine basis by Boxxer as an additional quality control measure.

Mr. Theodore A. DeMatties is an independent geologist consulting to Boxxer and is the Qualified Person who has reviewed and verified the technical information detailed in this release.

For further information please contact:

Colin Christensen, President
Telephone: 403-410-1303
Fax: 403-444-9494
Email: colin@boxxergold.com

Cavalcanti Hume Funfer Inc., Investor Relations
Cathy Hume, CEO
Phone: (416) 868-1079, Ext 23
cathy@chfir.com www.chfir.com

Jeanny So, Broker Relations Specialist
Phone: (416) 868-1079
jeanny@chfir.com www.chfir.com

If you wish to receive company press releases via email, please advise Alison Tullis at alison@chfir.com

The TSX Venture Exchange Does Not Accept Responsibility for the Adequacy or Accuracy of This Release

FORWARD-LOOKING STATEMENTS: Except for statements of historical fact, all statements in this news release – including, without limitation, statements regarding production estimates and future plans and objectives of Boxxer – are forward-looking statements that involve various risks and uncertainties. There can be no assurance that such statements will prove to be accurate; actual results and future events could differ materially from those anticipated in such statements.